Telefax: +49 (0) 6007 - 9382 390



Safety Data Sheet

according to UK REACH Regulation

pattern eXpress®

Revision date: 29.03.2023 Product code: 1-842 Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

pattern eXpress®

Product group: Liquid component
UFI: DJM1-MR3J-T60N-1NJQ

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Resin (powder component) for embedding in material and material tests.

1.3. Details of the supplier of the safety data sheet

Company name: AcrylX GmbH
Street: Industriestraße 7
Place: D-61191 Rosbach v.d.H.
Telephone: +49 (0) 6007 - 9382 300

e-mail: info@acrylx.com

Contact person: Oliver Wesner Telephone: 320

e-mail: info@acrylx.com Internet: www.acrylx.com

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Flam. Liq. 2; H225 Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 STOT SE 3; H335 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Methyl methacrylate

1,4-Butandiol dimethacrylate

2,2'-[(4-methylphenyl)imino]bisethanol

Signal word: Danger

Pictograms:





Hazard statements

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed. H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.



according to UK REACH Regulation

pattern eXpress®

Revision date: 29.03.2023 Product code: 1-842 Page 2 of 11

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smokina.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.

P370+P378 In case of fire: Use Foam, Extinguishing powder, Carbon dioxide (CO2) to extinguish.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container to as hazardous waste - in accordance with local and

national legislation - suitable, approved incinerator for combustible organic waste.

2.3. Other hazards

Polymerization with heat evolution may occur in the presence of radical forming substances (e.g. peroxides), reducing substances, and/or heavy metal ions.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture based on methyl methacrylate.

Hazardous components

CAS No	Chemical name			Quantity		
	EC No	Index No	REACH No			
	Classification (GB CLP Regulation)					
80-62-6	Methyl methacrylate			60 - < 65 %		
	201-297-1		01-2119452498-28			
	Flam. Liq. 2, Skin Irrit. 2, Skin Sens. 1, STOT SE 3; H225 H315 H317 H335					
72869-86-4	7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-	-3,14-dioxa-5,12-diazahexadecane-1	,16-diyl bismethacrylate	10 - < 15 %		
	276-957-5		01-2120751202-68			
	Skin Sens. 1B, Aquatic Chronic 2; H	H317 H411				
2082-81-7	1,4-Butandiol dimethacrylate					
	218-218-1		01-2119967415-30			
	Skin Sens. 1; H317					
3077-12-1	2,2'-[(4-methylphenyl)imino]bisethanol					
	221-359-1		01-2120791684-40			
	Acute Tox. 4, Eye Dam. 1; H302 H3	Acute Tox. 4, Eye Dam. 1; H302 H318				

Full text of H and EUH statements: see section 16.



Revision date: 29.03.2023

Safety Data Sheet

according to UK REACH Regulation

pattern eXpress®
Product code: 1-842

Page 3 of 11

Print date: 30.03.2023

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity		
	Specific Conc.	Limits, M-factors and ATE			
80-62-6	201-297-1	Methyl methacrylate			
	inhalation: LC5 mg/kg	nhalation: LC50 = 29,8 mg/l (vapours); dermal: LD50 = >5000 mg/kg; oral: LD50 = >5000 mg/kg			
2082-81-7	218-218-1	1,4-Butandiol dimethacrylate	5 - < 10 %		
	dermal: LD50	dermal: LD50 = > 3000 mg/kg; oral: LD50 = > 10000 mg/kg			
3077-12-1	221-359-1	2,2'-[(4-methylphenyl)imino]bisethanol	1 - < 5 %		
	oral: LD50 = >	300 mg/kg			

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated, saturated clothing immediately. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention.

After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Medical treatment necessary.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In case of skin irritation, consult a physician.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Do NOT induce vomiting. Rinse mouth. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Headache Dizziness Causes skin and eye irritation. Skin sensitisation

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2), Foam, Extinguishing powder

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Highly flammable liquid and vapour. Can polymerise exothermically if heated, exposed to air, sunlight or by addition or free radical initiators. Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures



according to UK REACH Regulation

pattern eXpress®

Revision date: 29.03.2023 Product code: 1-842 Page 4 of 11

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

When using do not eat, drink, smoke, sniff. Use only in well-ventilated areas. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Flammable vapours can accumulate in head space of closed systems. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Further information on handling

Caution! Transport usually takes place at temperatures above the flash point.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Protect from direct sunlight.

Hints on joint storage

Do not store together with: Material, oxygen-rich, Oxidising. Pyrophoric or self-heating substances.

Further information on storage conditions

Keep away from heat.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
80-62-6	Methyl methacrylate	50	208		TWA (8 h)	WEL
		100	416		STEL (15 min)	WEL



according to UK REACH Regulation

pattern eXpress®

Revision date: 29.03.2023 Product code: 1-842 Page 5 of 11

DNEL/DMEL values

CAS No	Substance					
DNEL type		Exposure route	Effect	Value		
80-62-6	Methyl methacrylate					
Worker DNEL,	long-term	inhalation		208 mg/m³		
Worker DNEL, long-term		dermal		17 mg/kg bw/day		

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: goggles.

Hand protection

Wear suitable protective gloves. To protect against splashes: butyl; EN 374. To protect against immersion: butyl; 0.7 mm or thicker, EN 374. The suitability of gloves should be agreed with the manufacturer. Change gloves in the event of contamination or if the breakthrough time is exceeded. Resistance of the glove material: see information from the glove manufacturer.

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Respiratory protection

Wear suitable respiratory protection if technical measures are inadequate or not available and exposure is to be expected that exceeds the DNEL (derived exposure level below which the substance does not cause any harm to human health). A suitable breathing mask with filter type A (EN141 or EN405) is recommended. A self-contained breathing apparatus may be necessary if particularly high vapor concentrations are formed.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: colourless
Odour: characteristic

Test method

Melting point/freezing point:

-48 °C

Boiling point or initial boiling point and

100,3 °C

boiling range:

Flammability: not applicable not applicable

Lower explosion limits: 2,1 vol. % Upper explosion limits: 12,5 vol. %

Flash point: 10 °C DIN 51755 Auto-ignition temperature: 435 °C DIN 51794

Decomposition temperature: not determined pH-Value: not determined Water solubility: 15,3 g/L

(at 20 °C)

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: log Pow 1,38 Vapour pressure: 37 hPa



according to UK REACH Regulation

pattern eXpress®

Revision date: 29.03.2023 Product code: 1-842 Page 6 of 11

Density (at 20 °C): 0,94 g/cm³ Relative vapour density: not determined

9.2. Other information

Information with regard to physical hazard classes

Self-ignition temperature

Solid: not applicable
Gas: not applicable

Oxidizing properties Not oxidising.

Other safety characteristics

Evaporation rate:

Solid content:

Viscosity / dynamic:
(at 20 °C)

not determined
not determined
0,53 mPa·s

Further Information

none

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable, Vapours can form explosive mixtures with air.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Can polymerise exothermically if heated, exposed to air, sunlight or by addition or free radical initiators.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Can polymerise exothermically if heated, exposed to air, sunlight or by addition or free radical initiators. Protect from direct sunlight.

10.5. Incompatible materials

Polymerization with heat evolution may occur in the presence of radical forming substances (e.g. peroxides), reducing substances, and/or heavy metal ions.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Harmful if swallowed.

ATEmix tested

	Dose	Species	Source
LD50, oral	> 5000 mg/kg	Rat	
LD50, dermal	> 5000 mg/kg	Rabbit	
LC50, inhalation (vapour) (1 h)	29,8 mg/l	Rat	



according to UK REACH Regulation

pattern eXpress®

Revision date: 29.03.2023 Product code: 1-842 Page 7 of 11

CAS No	Chemical name	Chemical name						
	Exposure route	Dose		Species	Source	Method		
80-62-6	Methyl methacrylate							
	oral	LD50 mg/kg	>5000	Rat	OECD 401			
	dermal	LD50 mg/kg	>5000	Rabbit				
	inhalation vapour	LC50	29,8 mg/l	Rat				
2082-81-7	1,4-Butandiol dimethacryl	ate						
	oral	LD50 mg/kg	> 10000	Rat				
	dermal	LD50 mg/kg	> 3000	Rabbit				
3077-12-1	2,2'-[(4-methylphenyl)imir	no]bisethano	l					
	oral	LD50 mg/kg	> 300	Rat				

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

May cause an allergic skin reaction. (Methyl methacrylate; 7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate; 1,4-Butandiol dimethacrylate)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (Methyl methacrylate)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

Acute (short-term) fish toxicity

Print date: 30.03.2023



Safety Data Sheet

according to UK REACH Regulation

pattern eXpress®

Revision date: 29.03.2023 Product code: 1-842 Page 8 of 11

CAS No	Chemical name	Chemical name						
	Aquatic toxicity	Dose	Dose		Species	Source	Method	
80-62-6	Methyl methacrylate	Methyl methacrylate						
	Acute fish toxicity	LC50 mg/l	> 79		Oncorhynchus mykiss (Rainbow trout)	OECD 203		
	Acute algae toxicity	ErC50 mg/l	> 110		Selenastrum capricornutum	OECD 201		
	Acute crustacea toxicity	EC50	69 mg/l		Daphnia magna (Big water flea)	OECD 202		
	Crustacea toxicity	NOEC	37 mg/l		Daphnia magna (Big water flea)	OECD 202		
2082-81-7	1,4-Butandiol dimethacryl	ate						
	Acute fish toxicity	LC50 mg/l	32,5		Oncorhynchus mykiss (Rainbow trout)			
	Acute crustacea toxicity	EC50 mg/l	7,51		Daphnia magna (Big water flea)	OECD 211		
	Crustacea toxicity	NOEC mg/l	7,51		Selenastrum capricornutum			

12.2. Persistence and degradability

Biodegradable.

12.3. Bioaccumulative potential

On the basis of existing data about the elimination/degradation and bioaccumulation potential longer term damage to the environment is unlikely.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
80-62-6	Methyl methacrylate	1,38
2082-81-7	1,4-Butandiol dimethacrylate	3,1

12.4. Mobility in soil

Mobility in soil: No adsoption in soil or sediment.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

070208 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of plastics, synthetic

rubber and man-made fibres; other still bottoms and reaction residues; hazardous waste



according to UK REACH Regulation

pattern eXpress®

Revision date: 29.03.2023 Product code: 1-842 Page 9 of 11

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1247

14.2. UN proper shipping name: METHYL METHACRYLATE MONOMER, STABILIZED

14.3. Transport hazard class(es): 14.4. Packing group: Ш Hazard label: 3 Classification code: F1 Limited quantity: 1 I Excepted quantity: F2 Transport category: 2 Hazard No: 339 Tunnel restriction code: D/F

Other applicable information (land transport)

SAPT: > 60 °C

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1247

14.2. UN proper shipping name: METHYL METHACRYLATE MONOMER, STABILIZED

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Classification code:F1Limited quantity:1 LExcepted quantity:E2

Other applicable information (inland waterways transport)

SAPT: > 60 °C

Marine transport (IMDG)

14.1. UN number or ID number: UN 1247

14.2. UN proper shipping name: METHYL METHACRYLATE MONOMER, STABILIZED

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Special Provisions:-Limited quantity:1 LExcepted quantity:E2EmS:F-E, S-D

Other applicable information (marine transport)

SAPT: > 60 °C

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1247

14.2. UN proper shipping name: METHYL METHACRYLATE MONOMER, STABILIZED

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Limited quantity Passenger:1 LPassenger LQ:Y341Excepted quantity:E2

IATA-packing instructions - Passenger: 353 IATA-max. quantity - Passenger: 5 L



according to UK REACH Regulation

pattern eXpress®

Revision date: 29.03.2023 Product code: 1-842 Page 10 of 11

IATA-packing instructions - Cargo: 364
IATA-max. quantity - Cargo: 60 L

Other applicable information (air transport)

SAPT: > 60 °C

14.6. Special precautions for user

Warning: Combustible liquid.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40

2010/75/EU (VOC): 64,5 % (606,3 g/l) 2004/42/EC (VOC): 64,5 % (606,3 g/l)

Information according to 2012/18/EU P5c FLAMMABLE LIQUIDS

(SEVESO III):

Additional information

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 3 - highly hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%



according to UK REACH Regulation

pattern eXpress®

Revision date: 29.03.2023 Product code: 1-842 Page 11 of 11

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Acute Tox. 4; H302	
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
STOT SE 3; H335	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

	,
H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)



according to UK REACH Regulation

pattern eXpress®

Revision date: 21.11.2022 Product code: 1-841 Page 1 of 7

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

pattern eXpress®

Product group: Powder component
UFI: W7X1-TR3E-E60K-S7E0

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Resin (powder component) for embedding in material and material tests.

1.3. Details of the supplier of the safety data sheet

Company name: AcrylX GmbH
Street: Industriestraße 7
Place: D-61191 Rosbach v.d.H.

Telephone: +49 (0) 6007 - 9382 300 Telefax: +49 (0) 6007 - 9382 390

e-mail: info@acrylx.com

Contact person: Oliver Wesner Telephone: 320

e-mail: info@acrylx.com Internet: www.acrylx.com

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Skin Sens. 1; H317 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

dibenzoyl peroxide; benzoyl peroxide

Signal word: Warning

Pictograms:



Hazard statements

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contents/container to as hazardous waste - in accordance with local and

national legislation - suitable, approved incinerator for combustible organic waste.

Print date: 30.03.2023



Safety Data Sheet

according to UK REACH Regulation

pattern eXpress®

Revision date: 21.11.2022 Product code: 1-841 Page 2 of 7

2.3. Other hazards

Contains methyl methacrylate, dibenzoyl peroxide. Can cause allergic reactions.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture based on polymethyl methacrylates and catalyst.

Hazardous components

CAS No	Chemical name			Quantity			
	EC No	Index No	REACH No				
	Classification (GB CLP Regulation	Classification (GB CLP Regulation)					
9011-14-7	Acrylic polymer	Acrylic polymer					
94-36-0	dibenzoyl peroxide; benzoyl perox	de		1 - < 5 %			
	202-327-6		01-2119511472-50				
	Org. Perox. B, Eye Irrit. 2, Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 1; H241 H319 H317 H400 H410						

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Get medical advice/attention if you feel unwell.

After inhalation

Provide fresh air.

After contact with skin

Wash with plenty of water. Take off contaminated clothing and wash it before reuse.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

After ingestion

Rinse mouth immediately and drink plenty of water.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam Extinguishing powder Carbon dioxide (CO2)

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide, Carbon dioxide

5.3. Advice for firefighters



according to UK REACH Regulation

pattern eXpress®

Revision date: 21.11.2022 Product code: 1-841 Page 3 of 7

In case of fire: Wear self-contained breathing apparatus.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation. Avoid dust formation. Do not breathe dust. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Other information

Take up mechanically. Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

No special measures are necessary.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or dripk

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed.

Hints on joint storage

No special measures are necessary.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
94-36-0	Dibenzoyl peroxide	-	5		TWA (8 h)	WEL

8.2. Exposure controls

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection.

Hand protection

Authorisation No.



according to UK REACH Regulation

pattern eXpress®

Revision date: 21.11.2022 Product code: 1-841 Page 4 of 7

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

A suitable dust mask or respirator with filter type P1 or FFP1 (EN143 or EN149) may be suitable. In the unlikely event that particularly large amounts of dust are formed, a self-contained breathing apparatus may be appropriate.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Powder
Colour: see packing
Odour: characteristic

Melting point/freezing point:

Ca. 110 °C

Boiling point or initial boiling point and

not determined

boiling range:

Flammability: not determined not applicable

Lower explosion limits:not determinedUpper explosion limits:not determinedFlash point:> 250 °CAuto-ignition temperature:> 400 °CDecomposition temperature:not determinedpH-Value:not determined

Water solubility:

The study does not need to be conducted because the substance is known to be

insoluble in water.

Solubility in other solvents

Soluble in hydrocarbons.

Partition coefficient n-octanol/water:

Vapour pressure:

Density (at 20 °C):

Bulk density (at 20 °C):

Relative vapour density:

not determined

1,16 g/cm³

700 - 750 kg/m³

not determined

9.2. Other information

Information with regard to physical hazard classes

Self-ignition temperature

Solid: not determined Gas: not applicable

Oxidizing properties Not oxidising.

Other safety characteristics

Evaporation rate: not determined Solid content: 100 %

SECTION 10: Stability and reactivity

10.1. Reactivity

oxidising, Oxidising.

10.2. Chemical stability

May cause decomposition by long-term light influence. The product is stable under storage at normal ambient



according to UK REACH Regulation

pattern eXpress®

Revision date: 21.11.2022 Product code: 1-841 Page 5 of 7

temperatures.

10.3. Possibility of hazardous reactions

Exothermic reaction with: Combustible substance, Alkali metals, Alkaline earth metal, Heavy metals, Metal powder, Acid, Base.

10.4. Conditions to avoid

none

10.5. Incompatible materials

Keep away from combustible material.

10.6. Hazardous decomposition products

Formation of: Oxygen. Exothermal decomposition with formation of: Methyl methacrylate

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Toxicocinetics, metabolism and distribution

Toxicological data are not available.

Acute toxicity

Based on available data, the classification criteria are not met.

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

May cause an allergic skin reaction. (dibenzoyl peroxide; benzoyl peroxide)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

The product is not: Ecotoxic.

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Print date: 30.03.2023



Safety Data Sheet

according to UK REACH Regulation

pattern eXpress®

Revision date: 21.11.2022 Product code: 1-841 Page 6 of 7

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number or ID number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number or ID number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Information according to 2012/18/EU Not subj

(SEVESO III):

Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.



according to UK REACH Regulation

pattern eXpress®

Revision date: 21.11.2022 Product code: 1-841 Page 7 of 7

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H241	Heating may cause a fire or explosion.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)