

## Safety Data Sheet

according to UK REACH Regulation

### MegaBase Adhesive

Revision date: 30.01.2024

Product code: -D5038220NA-

Page 1 of 11

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

MegaBase Adhesive

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Adhesive

Medical device for use in dentistry, observe instructions for use.

#### Uses advised against

Use by untrained dental personnel and/or unapproved areas of application.

### 1.3. Details of the supplier of the safety data sheet

Company name: 4dentPro GmbH & Co. KG  
Street: Wehrshäuser Str. 2b  
Place: D-35041 Marburg  
e-mail (Contact person): service@4dentpro.com  
Internet: www.4dentpro.com

### 1.4. Emergency telephone number:

+49 800 330 3315

### Further Information

The product is intended for professional use.

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### GB CLP Regulation

Flam. Liq. 2; H225

Eye Irrit. 2; H319

Skin Sens. 1; H317

STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

\*Safety Information Sheet for Medical Devices\* The particulars given in the Safety Information Sheet only apply to the described product in connection with its appropriate utilization. These particulars are based on the latest state of our knowledge and information. They serve the purpose of describing our product under the aspect of hazards caused by such product and pertaining safety actions. They do not constitute any guarantee of product quality and/or quality features. The particulars given in this Safety Information Sheet are not required according to the Article 31 and Annex II of Regulation (EC) No 1907/2006 (REACH Regulation). This product is classified as a medical device. Medical devices are exempt from the labelling provisions. They merely serve the purpose of providing sufficient information on the voluntary basis with a view to ensure the safe utilization of such substance/mixture/product.

### 2.2. Label elements

#### GB CLP Regulation

#### Hazard components for labelling

ethyl acetate

methyl methacrylate

#### Signal word:

Danger

#### Pictograms:



## Safety Data Sheet

according to UK REACH Regulation

### MegaBase Adhesive

Revision date: 30.01.2024

Product code: -D5038220NA-

Page 2 of 11

#### Hazard statements

H225	Highly flammable liquid and vapour.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

#### Precautionary statements

P501	Dispose of contents/container in accordance with local/regional/national international regulations.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P403+P235	Store in a well-ventilated place. Keep cool.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P302+P352	IF ON SKIN: Wash with plenty of water.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.

#### Special labelling of certain mixtures

95 - < 100 % of the mixture consists of ingredient(s) of unknown acute toxicity (inhalation).  
Contains < 1 % of components with unknown hazards to the aquatic environment.

#### 2.3. Other hazards

Formation of potentially explosive vapor/air mixtures is possible.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Chemical characterization

Polymethyl methacrylate Copolymer in ethyl acetate.

##### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
141-78-6	ethyl acetate			95 - < 100 %
	205-500-4	607-022-00-5	01-2119475103-46	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
80-62-6	methyl methacrylate			1 - < 5 %
	201-297-1	607-035-00-6		
	Flam. Liq. 2, Skin Irrit. 2, Skin Sens. 1, STOT SE 3; H225 H315 H317 H335			
1330-20-7	xylene			< 1 %
	215-535-7	601-022-00-9	01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2; H226 H332 H312 H315			

Full text of H and EUH statements: see section 16.

##### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
141-78-6	205-500-4	ethyl acetate	95 - < 100 %
		inhalation: Data lacking (gases); dermal: LD50 = >20000 mg/kg; oral: LD50 = 5620 mg/kg	
1330-20-7	215-535-7	xylene	< 1 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: ATE = 1100 mg/kg	

## Safety Data Sheet

according to UK REACH Regulation

### MegaBase Adhesive

Revision date: 30.01.2024

Product code: -D5038220NA-

Page 3 of 11

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

#### After inhalation

Provide fresh air.

Seek medical attention if problems persist.

#### After contact with skin

After contact with skin, wash immediately with plenty of water and soap.

Change contaminated clothing.

#### After contact with eyes

If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an ophthalmologist.

#### After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.

Do NOT induce vomiting. Caution if victim vomits: Risk of aspiration!

Have victim drink large quantities of water, with active charcoal if possible. Give sodium sulfate as laxative (1 tablespoon in 1 glass of water).

### 4.2. Most important symptoms and effects, both acute and delayed

No known symptoms to date.

### 4.3. Indication of any immediate medical attention and special treatment needed

No data available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

All standard extinguishing agents are suitable.

Extinguishing powder

Foam

Carbon dioxide (CO<sub>2</sub>)

#### Unsuitable extinguishing media

Avoid water in straight hose stream; will scatter and spread fire.

### 5.2. Special hazards arising from the substance or mixture

Combustible. Vapours are heavier than air and will spread at floor level.

### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

#### Additional information

Take precautionary measures against static discharges.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Remove all sources of ignition.

Use personal protection equipment.

#### For non-emergency personnel

Do not allow to enter into surface water or drains.

## Safety Data Sheet

according to UK REACH Regulation

### MegaBase Adhesive

Revision date: 30.01.2024

Product code: -D5038220NA-

Page 4 of 11

#### **6.2. Environmental precautions**

Do not allow to enter into surface water or drains.

#### **6.3. Methods and material for containment and cleaning up**

##### **For containment**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

##### **Other information**

Wipe up with absorbent material (eg. cloth, fleece). Clean contaminated articles and floor according to the environmental legislation.

#### **6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Section 12: Ecological Information (non-mandatory)

## **SECTION 7: Handling and storage**

#### **7.1. Precautions for safe handling**

##### **Advice on safe handling**

Wear personal protection equipment (refer to section 8).

Avoid breathing vapours.

##### **Advice on protection against fire and explosion**

Take precautionary measures against static discharges.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

##### **Advice on general occupational hygiene**

Avoid contact with skin, eyes and clothes.

When using do not eat, drink, smoke, sniff.

##### **Further information on handling**

Keep locked up and out of reach of children.

#### **7.2. Conditions for safe storage, including any incompatibilities**

##### **Requirements for storage rooms and vessels**

After use replace the closing cap immediately.

Keep only in the original container.

Keep container tightly closed in a cool, well-ventilated place.

##### **Hints on joint storage**

Keep away from food and drink.

##### **Further information on storage conditions**

Please pay attention to the information on the package!

#### **7.3. Specific end use(s)**

Not applicable.

## **SECTION 8: Exposure controls/personal protection**

#### **8.1. Control parameters**

## Safety Data Sheet

according to UK REACH Regulation

### MegaBase Adhesive

Revision date: 30.01.2024

Product code: -D5038220NA-

Page 5 of 11

#### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
141-78-6	Ethyl acetate	200	734		TWA (8 h)	WEL
		400	1468		STEL (15 min)	WEL
80-62-6	Methyl methacrylate	50	208		TWA (8 h)	WEL
		100	416		STEL (15 min)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

#### Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid (creatinine)	650 mmol/mol	urine	Post shift

#### 8.2. Exposure controls

##### Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment. If handled uncovered, arrangements with local exhaust ventilation have to be used.

##### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Eye glasses with side protection EN 166

##### Hand protection

When handling with chemical substances, protective clothing with CE-labels including the four control digits must be worn. Recommended glove articles EN ISO 374

By short-term hand contact Suitable material: NBR (Nitrile rubber).

Thickness of the glove material: 0,38mm

Breakthrough time:: -

By long-term hand contact: PE (polyethylene)

Thickness of the glove material: -

Breakthrough time:: >480 min

##### Skin protection

Protective clothing.

Avoid contact with skin, eyes and clothes.

Take off contaminated clothing and wash it before reuse.

##### Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required. Provide adequate ventilation.

Respiratory protection necessary at: aerosol or mist generation.

Suitable respiratory protection apparatus: Full-/half-/quarter-face masks (EN 136/140)

Suitable material: A2, B2, E2, K2, P3

##### Environmental exposure controls

Do not allow to enter into surface water or drains.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	colourless
Odour:	characteristic

## Safety Data Sheet

according to UK REACH Regulation

### MegaBase Adhesive

Revision date: 30.01.2024

Product code: -D5038220NA-

Page 6 of 11

Odour threshold: No data available

		<b>Test method</b>
Melting point/freezing point:	-84 °C	
Boiling point or initial boiling point and boiling range:	76,5 - 77,5 °C	
Flammability:	No data available	ISO 10156
Lower explosion limits:	2,1 vol. %	
Upper explosion limits:	11,5 vol. %	
Flash point:	ca. - 4 °C	DIN 51758
Auto-ignition temperature:	No data available	
Decomposition temperature:	No data available	
pH-Value:	not applicable	
Viscosity / kinematic:	No data available	
Water solubility: (at 20 °C)	ca. 85 g/L	
Dissolution rate:	No data available	
Partition coefficient n-octanol/water:	0,73	
Dispersion stability:	No data available	
Vapour pressure: (at 20 °C)	No data available	
Vapour pressure:	No data available	
Density (at 20 °C):	> 0,9 g/cm <sup>3</sup>	
Relative density:	No data available	
Bulk density:	not applicable	
Relative vapour density: (at 20 °C)	No data available	g/cm <sup>3</sup>
Particle characteristics:	not applicable	

#### **9.2. Other information**

##### **Information with regard to physical hazard classes**

###### Explosive properties

Formation of potentially explosive vapor/air mixtures is possible.

###### Sustaining combustion:

No data available

###### Self-ignition temperature

Solid:

not applicable

Gas:

not applicable

###### Oxidizing properties

none

##### **Other safety characteristics**

###### Viscosity / dynamic:

0,44 mPa·s

## **SECTION 10: Stability and reactivity**

### **10.1. Reactivity**

Vapours can form explosive mixtures with air.

### **10.2. Chemical stability**

The product is chemically stable under recommended conditions of storage, use and temperature.

### **10.3. Possibility of hazardous reactions**

None by intended use.

### **10.4. Conditions to avoid**

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

**Safety Data Sheet**

according to UK REACH Regulation

**MegaBase Adhesive**

Revision date: 30.01.2024

Product code: -D5038220NA-

Page 7 of 11

**10.5. Incompatible materials**

Alkali metals.  
Oxidizing agents.

**10.6. Hazardous decomposition products**

No data available

**Further information**

Highly flammable. Vapours may form explosive mixtures with air.

**SECTION 11: Toxicological information**

**11.1. Information on hazard classes as defined in GB CLP Regulation**

**Acute toxicity**

Based on available data, the classification criteria are not met.  
Acute toxicity, oral: LD50: > 5000 mg/kg Rat

**ATEmix tested**

	Dose	Species	Source
LD50, oral	5000 mg/kg	Rat	
LD50, dermal	18000 mg/kg	Rabbit	
LC50, inhalation (vapour)	mg/l	not applicable	

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
141-78-6	ethyl acetate				
	oral	LD50 5620 mg/kg	Rat		
	dermal	LD50 >20000 mg/kg	Rabit		
	inhalation	Data lacking			
1330-20-7	xylene				
	dermal	ATE 1100 mg/kg			
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			

**Irritation and corrosivity**

Causes serious eye irritation.  
Skin corrosion/irritation: Based on available data, the classification criteria are not met.  
Skin corrosion/irritation: not applicable

**Sensitising effects**

May cause an allergic skin reaction. (methyl methacrylate)  
no danger of sensitization.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause drowsiness or dizziness. (ethyl acetate)

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**11.2. Information on other hazards**

## Safety Data Sheet

according to UK REACH Regulation

### MegaBase Adhesive

Revision date: 30.01.2024

Product code: -D5038220NA-

Page 8 of 11

#### Further information

Harmful by inhalation and if swallowed.

Hazards identification: Nausea. Headache. Vapours may cause drowsiness and dizziness.

After skin contact: Has de-greasing effect on the skin.

Following eye contact: Irritant.

Harmful: may cause lung damage if swallowed. pneumonia.

## SECTION 12: Ecological information

### 12.1. Toxicity

Based on available data, the classification criteria are not met.

Toxic to aquatic organisms.

Technically correct releases of minimal concentrations to adapted biological sewage treatment facility, will not disturb the biodegradability of activated sludge.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
141-78-6	ethyl acetate					
	Acute fish toxicity	LC50	230 mg/l	96 h	Pimephales promelas	
	Acute algae toxicity	ErC50	>100 mg/l	72 h	Desmodesmus subspicatus	

### 12.2. Persistence and degradability

No data available

### 12.3. Bioaccumulative potential

No indication of bio-accumulation potential.

#### BCF

CAS No	Chemical name	BCF	Species	Source
141-78-6	ethyl acetate	30		

### 12.4. Mobility in soil

The product has not been tested.

### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

### 12.7. Other adverse effects

None known.

#### Further information

Do not allow uncontrolled leakage of product into the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Disposal recommendations

Do not remove with domestic waste.

#### List of Wastes Code - residues/unused products

180106 WASTES FROM HUMAN OR ANIMAL HEALTH CARE AND/OR RELATED RESEARCH (EXCEPT KITCHEN AND RESTAURANT WASTES NOT ARISING FROM IMMEDIATE HEALTH CARE); wastes from natal care, diagnosis, treatment or prevention of disease in humans; chemicals consisting of or containing hazardous substances; hazardous waste

## Safety Data Sheet

according to UK REACH Regulation

### MegaBase Adhesive

Revision date: 30.01.2024

Product code: -D5038220NA-

Page 9 of 11

#### List of Wastes Code - used product

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

#### List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

#### Contaminated packaging

Cleaned containers may be recycled.

### SECTION 14: Transport information

#### Land transport (ADR/RID)

**14.1. UN number or ID number:** UN 1173  
**14.2. UN proper shipping name:** ETHYL ACETATE  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3



Classification code: F1  
 Limited quantity: 1 L  
 Excepted quantity: E2  
 Transport category: 2  
 Hazard No: 33  
 Tunnel restriction code: D/E

#### Inland waterways transport (ADN)

**14.1. UN number or ID number:** UN 1173  
**14.2. UN proper shipping name:** ETHYL ACETATE  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3



Classification code: F1  
 Limited quantity: 1 L  
 Excepted quantity: E2

#### Marine transport (IMDG)

**14.1. UN number or ID number:** UN 1173  
**14.2. UN proper shipping name:** ETHYL ACETATE  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3



## Safety Data Sheet

according to UK REACH Regulation

### MegaBase Adhesive

Revision date: 30.01.2024

Product code: -D5038220NA-

Page 10 of 11

Special Provisions: -  
 Limited quantity: 1 L  
 Excepted quantity: E2  
 EmS: F-E, S-D

#### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number or ID number:** UN 1173  
**14.2. UN proper shipping name:** ETHYL ACETATE  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3



Limited quantity Passenger: 1 L  
 Passenger LQ: Y341  
 Excepted quantity: E2  
 IATA-packing instructions - Passenger: 353  
 IATA-max. quantity - Passenger: 5 L  
 IATA-packing instructions - Cargo: 364  
 IATA-max. quantity - Cargo: 60 L

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No  
 Danger releasing substance: Not applicable.

#### 14.6. Special precautions for user

not relevant

#### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulatory information

Restrictions on use (REACH, annex XVII):  
 Entry 3, Entry 40, Entry 75

##### Additional information

The classification was undertaken in accordance with the calculation method governed by the Preparations Directive (1999/45/EC).

##### National regulatory information

Water hazard class (D): 3 - highly hazardous to water

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information

#### Changes

This data sheet contains changes from the previous version in section(s): 2,5,11,16.

Date of preparation / Revised on: 30/01/2024

Version number: 1,01

Replaces version number: 1,00 (03/03/2021)

## Safety Data Sheet

according to UK REACH Regulation

### MegaBase Adhesive

Revision date: 30.01.2024

Product code: -D5038220NA-

Page 11 of 11

#### Abbreviations and acronyms

ATE: Acute toxicity estimate. CAS: Chemical abstracts service. CFR: Code of Federal Regulations. DNEL: Derived No Effect Level EC50: 50% of maximal effective concentration. FDA: Food and Drug Administration. GHS: Globally Harmonised System. IATA: International air transport association. ICAO: Technical instructions for the safe transport of dangerous goods by air. IMDG: International maritime dangerous goods. LC50: Lethal concentration to 50 % of a test population. LD50: Lethal dose to 50% of a test population (median lethal dose). NOAEL: No Observed Adverse Effect Level. PBT: Persistent, bioaccumulative and toxic substance. PEL: Permissible Exposure Limit. PNEC: Predicted No Effect Concentration. REL: Recommended exposure limit. STOT RE: Specific Target Organ Toxicity – Single Exposure. STOT SE: Specific Target Organ Toxicity – Repeated Exposure. TWA: 8-hour Time Weighted Averages (long-term exposure limit). US OSHA: US Occupational Safety and Health Administration. vPvB: Very persistent and very bioaccumulative.

#### Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
STOT SE 3; H336	Calculation method

#### Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

#### Further Information

Training instructions: Use only by personnel trained in dentistry.

Disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*