according to Regulation (EC) No 1907/2006

Revision date: 14.10.2022	Product coc	de: 00320-0160-GHS	Page 1 of 10
SECTION 1: Identificatio	n of the substance/mixture and	d of the company/undertaking	
.1. Product identifier			
Septasol			
	s of the substance or mixture and	<u>d uses advised against</u>	
Use of the substance/m Hand disinfectant for			
.3. Details of the supplier			
Company name:	Miscea GmbH		
Street: Place:	Hauptstraße 2 14979 Großbeeren		
Telephone:	+49 (0) 33701/3553-0	Telefax: +49 (0) 33701/3	553-19
e-mail:	berlin@miscea.com		
Responsible Department	Responsible for the sa	ifety data sheet: sds@gbk-ingelheim.de	
I.4. Emergency telephone		9 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365	ōd/a)
number:	In England and Wales:	: NHS 111 In Scotland: NHS 24 - dial 111	
SECTION 2: Hazards ide	ntification		
2.1. Classification of the su	bstance or mixture		
Regulation (EC) No. 127	2/2008		
Regulation (EC) No. 127 Hazard categories:	2/2008		
Hazard categories: Flammable liquids: F	am. Liq. 3		
Hazard categories: Flammable liquids: F Serious eye damage	am. Liq. 3 eye irritation: Eye Irrit. 2		
Hazard categories: Flammable liquids: F Serious eye damage Specific target organ	am. Liq. 3	Е 3	
Hazard categories: Flammable liquids: F Serious eye damage Specific target organ Hazard Statements:	am. Liq. 3 eye irritation: Eye Irrit. 2 toxicity - single exposure: STOT SE	E 3	
Hazard categories: Flammable liquids: F Serious eye damage Specific target organ Hazard Statements: Flammable liquid and	am. Liq. 3 eye irritation: Eye Irrit. 2 toxicity - single exposure: STOT SE vapour.	Е 3	
Hazard categories: Flammable liquids: F Serious eye damage Specific target organ Hazard Statements: Flammable liquid and Causes serious eye	am. Liq. 3 eye irritation: Eye Irrit. 2 toxicity - single exposure: STOT SE vapour. ritation.	E 3	
Hazard categories: Flammable liquids: F Serious eye damage Specific target organ Hazard Statements: Flammable liquid and Causes serious eye May cause drowsine	am. Liq. 3 eye irritation: Eye Irrit. 2 toxicity - single exposure: STOT SE vapour. ritation.	E 3	
Hazard categories: Flammable liquids: F Serious eye damage Specific target organ Hazard Statements: Flammable liquid and Causes serious eye May cause drowsine	am. Liq. 3 eye irritation: Eye Irrit. 2 toxicity - single exposure: STOT SE vapour. ritation. s or dizziness.	Ε3	
Hazard categories: Flammable liquids: F Serious eye damage Specific target organ Hazard Statements: Flammable liquid and Causes serious eye May cause drowsine 2.2. Label elements Regulation (EC) No. 127 Hazard components for	am. Liq. 3 eye irritation: Eye Irrit. 2 toxicity - single exposure: STOT SE vapour. ritation. s or dizziness. 2/2008	E 3	
Hazard categories: Flammable liquids: F Serious eye damage Specific target organ Hazard Statements: Flammable liquid and Causes serious eye May cause drowsine 2.2. Label elements Regulation (EC) No. 127	am. Liq. 3 eye irritation: Eye Irrit. 2 toxicity - single exposure: STOT SE vapour. ritation. s or dizziness. 2/2008	Ε3	
Hazard categories: Flammable liquids: F Serious eye damage Specific target organ Hazard Statements: Flammable liquid and Causes serious eye May cause drowsine 2.2. Label elements Regulation (EC) No. 127 Hazard components for Propan-2-ol	am. Liq. 3 eye irritation: Eye Irrit. 2 toxicity - single exposure: STOT SE vapour. ritation. s or dizziness. 2/2008 labelling	E 3	
Hazard categories: Flammable liquids: F Serious eye damage Specific target organ Hazard Statements: Flammable liquid and Causes serious eye May cause drowsine 2.2. Label elements Regulation (EC) No. 127 Hazard components for Propan-2-ol Signal word:	am. Liq. 3 eye irritation: Eye Irrit. 2 toxicity - single exposure: STOT SE vapour. ritation. s or dizziness. 2/2008 labelling	Ε3	
Hazard categories: Flammable liquids: F Serious eye damage Specific target organ Hazard Statements: Flammable liquid and Causes serious eye May cause drowsine 2.2. Label elements Regulation (EC) No. 127 Hazard components for Propan-2-ol Signal word:	am. Liq. 3 eye irritation: Eye Irrit. 2 toxicity - single exposure: STOT SE vapour. ritation. s or dizziness. 2/2008 labelling	Ε3	
Hazard categories: Flammable liquids: F Serious eye damage Specific target organ Hazard Statements: Flammable liquid and Causes serious eye May cause drowsine 2.2. Label elements Regulation (EC) No. 127 Hazard components for Propan-2-ol Signal word:	am. Liq. 3 eye irritation: Eye Irrit. 2 toxicity - single exposure: STOT SE vapour. ritation. s or dizziness. 2/2008 labelling	Ε3	
Hazard categories: Flammable liquids: F Serious eye damage Specific target organ Hazard Statements: Flammable liquid and Causes serious eye May cause drowsine 2.2. Label elements Regulation (EC) No. 127 Hazard components for Propan-2-ol Signal word: Pictograms:	am. Liq. 3 eye irritation: Eye Irrit. 2 toxicity - single exposure: STOT SE vapour. ritation. s or dizziness. 2/2008 labelling	E 3	
Hazard categories: Flammable liquids: F Serious eye damage Specific target organ Hazard Statements: Flammable liquid and Causes serious eye May cause drowsine 2.2. Label elements Regulation (EC) No. 127 Hazard components for Propan-2-ol Signal word: Pictograms: Hazard statements H226 H319	am. Liq. 3 eye irritation: Eye Irrit. 2 toxicity - single exposure: STOT SE vapour. ritation. s or dizziness. 2/2008 labelling Warning Warning Flammable liquid and vapour. Causes serious eye irritation.		
Hazard categories: Flammable liquids: F Serious eye damage Specific target organ Hazard Statements: Flammable liquid and Causes serious eye May cause drowsine 2.2. Label elements Regulation (EC) No. 127 Hazard components for Propan-2-ol Signal word: Pictograms: Hazard statements H226	am. Liq. 3 eye irritation: Eye Irrit. 2 toxicity - single exposure: STOT SE vapour. ritation. s or dizziness. 2/2008 labelling Warning Warning Flammable liquid and vapour.		
Hazard categories: Flammable liquids: F Serious eye damage Specific target organ Hazard Statements: Flammable liquid and Causes serious eye May cause drowsine 2.2. Label elements Regulation (EC) No. 127 Hazard components for Propan-2-ol Signal word: Pictograms: Hazard statements H226 H319	am. Liq. 3 eye irritation: Eye Irrit. 2 toxicity - single exposure: STOT SE vapour. ritation. s or dizziness. 2/2008 labelling Warning Warning Flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizzines		
Hazard categories: Flammable liquids: F Serious eye damage Specific target organ Hazard Statements: Flammable liquid and Causes serious eye May cause drowsine 2.2. Label elements Regulation (EC) No. 127 Hazard components for Propan-2-ol Signal word: Pictograms: Hazard statements H226 H319 H336 Precautionary statemer P101	am. Liq. 3 eye irritation: Eye Irrit. 2 toxicity - single exposure: STOT SE vapour. ritation. so or dizziness. 2/2008 labelling Warning Warning Flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizzines ts If medical advice is needed, have		
Hazard categories: Flammable liquids: F Serious eye damage Specific target organ Hazard Statements: Flammable liquid and Causes serious eye May cause drowsine 2.2. Label elements Regulation (EC) No. 127 Hazard components for Propan-2-ol Signal word: Pictograms: Hazard statements H226 H319 H336 Precautionary statement P101 P102	am. Liq. 3 eye irritation: Eye Irrit. 2 toxicity - single exposure: STOT SE vapour. ritation. is or dizziness. 2/2008 labelling Warning Warning Flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizzines is If medical advice is needed, have Keep out of reach of children.	ess.	
Hazard categories: Flammable liquids: F Serious eye damage Specific target organ Hazard Statements: Flammable liquid and Causes serious eye f May cause drowsine 2.2. Label elements Regulation (EC) No. 127 Hazard components for Propan-2-ol Signal word: Pictograms: Hazard statements H226 H319 H336 Precautionary statement P101	am. Liq. 3 eye irritation: Eye Irrit. 2 toxicity - single exposure: STOT SE vapour. ritation. s or dizziness. 2/2008 labelling Warning Warning Flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizzines ts If medical advice is needed, have Keep out of reach of children. Keep away from heat, hot surface	PSS.	. No
Hazard categories: Flammable liquids: F Serious eye damage Specific target organ Hazard Statements: Flammable liquid and Causes serious eye f May cause drowsine 2.2. Label elements Regulation (EC) No. 127 Hazard components for Propan-2-ol Signal word: Pictograms: Hazard statements H226 H319 H336 Precautionary statement P101 P102	am. Liq. 3 eye irritation: Eye Irrit. 2 toxicity - single exposure: STOT SE vapour. ritation. is or dizziness. 2/2008 labelling Warning Warning Flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizzines is If medical advice is needed, have Keep out of reach of children.	ess.	. No

according to Regulation (EC) No 1907/2006

		Septas	ol	
Revision date: 14.10.2	022	Product code: 003		Page 2 of 10
	present and eas	sy to do. Continue rinsing		
P501	Dispose of cont	tents/container to in acco	rdance with local and national regulation	ons.
2.3. Other hazards				
According to Re PBT / vPvB sub	• • • •	/2006 (REACH) none of	the substances, contained in this produ	uct are a
REACH for hav in accordance v Regulation (EU	ing endocrine disrupting vith the criteria set out i	g properties, or is not ide in Commission Delegated	stablished in accordance with Article 5 ntified as having endocrine disrupting p I Regulation (EU) 2017/2100 or Comm	properties
SECTION 3: Compo 3.2. Mixtures	sition/information o	n ingredients		
Chemical characte Alcoholic soluti Hazardous compone	on			
	Chemical name			Quantity
EC No		Index No	REACH No	
GHS C	assification		ł	
	Propan-2-ol			60 - 65 %
67-63-0 Propan	- •.			00 00 /0
67-63-0 Propan 200-66		603-117-00-0	01-2119457558-25	

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately. If you feel unwell, seek medical advice.

After inhalation

Move to fresh air in case of accidental inhalation of vapours. In the event of symptoms refer for medical treatment.

After contact with skin

No special measure necessary.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.

After ingestion

Summon a doctor immediately. Rinse out mouth and give plenty of water to drink. Never give anything by mouth to an unconscious person. Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

Causes serious eye irritation. May cause drowsiness or dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

according to Regulation (EC) No 1907/2006

Septasol

Revision date: 14.10.2022

Product code: 00320-0160-GHS

Page 3 of 10

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO2), water-spray.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Fire may produce:

carbon monoxide and carbon dioxide

5.3. Advice for firefighters

Use breathing apparatus with independent air supply. Protective suit.

Protective suit.

Additional information

Keep away from sources of ignition - No smoking. Vapours are heavier than air and spread along ground. The vapour/air mixture is explosive, even in empty, uncleaned receptacles. Cool containers at risk with water spray jet. Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Ensure adequate ventilation. Keep away sources of ignition. Keep away noninvolved persons.

For non-emergency personnel

Do not breathe vapours. Avoid contact with skin, eyes and clothing.

For emergency responders

In case of vapour formation use respirator. Use personal protective clothing.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder). Shovel into suitable container for disposal.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8). Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep tightly closed. Use only in thoroughly ventilated areas.

according to Regulation (EC) No 1907/2006

		S	eptasol				
Revision da	te: 14.10.2022	Product co	de: 00320-0	160-GHS			Page 4 of 10
Do n	on protection against fire and ex ot smoke - volatile. o product and empty container aw	-	sources of i	nition.			
<u>7.2. Conditi</u>	ons for safe storage, including	any incompatibilit	<u>ties</u>				
•	ments for storage rooms and ve o container tightly closed in a dry,		tilated place				
	i joint storage npatible with oxidizing agents.						
	information on storage condition a way from food, drink and anim						
7.3. Specifi	<u>c end use(s)</u>						
Hand	d disinfectant for professional use	•					
SECTION	8: Exposure controls/person	al protection					
8.1. Contro	parameters						
Exposure li	mits (EH40)						
CAS No	Substance		ppm	mg/m³	fibres/ml	Category	Origin
67-63-0	Propan-2-ol		400	999		TWA (8 h)	WEL
			500	1250		STEL (15 min)	WEL

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

When using do not eat, drink or smoke. Remove and wash contaminated clothes before re-use. Do not breath vapours or spray mist. Avoid contact with eyes.

Eye/face protection

Safety goggles with side protection (EN 166). Eye wash bottle with pure water (EN 15154).

Hand protection

Protective gloves resistant to chemicals made off butyl, minimum coat thickness 0.7 mm, permeation resistance approx. 480 minutes, i.e. protective glove <Butoject 898> made by www.kcl.de. Protective gloves resistant to chemicals made off viton, minimum coat thickness 0.7 mm, permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Vitoject 890> made by www.kcl.de. This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Skin protection

Long sleeved clothing (DIN EN ISO 6530)

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

according to Regulation (EC) No 1907/2006

Revision date: 14.10.2022	Septasol Product code: 00320-0160-GHS	Page 5 of 10		
SECTION 9: Physical and chemica	al properties			
9.1. Information on basic physical an	d chemical properties			
Physical state:	Liquid			
Colour:	Colourless			
Odour:	Alcoholic			
pH-Value (at 20 °C):	7 - 8,6			
Changes in the physical state Melting point/freezing point:	< - 20 °C			
Boiling point or initial boiling point a boiling range:				
Sublimation point:	n.a.			
Softening point:	n.d.			
Flash point:	24 °C			
Sustaining combustion:	Sustaining combustion			
Flammability				
Solid/liquid: Gas:	n.a.			
Explosive properties	n.a.			
	explosive; nevertheless explosive vapour/air mixture can be get	nerated.		
Lower explosion limits:	2 vol. %			
Upper explosion limits:	n.d.			
Auto-ignition temperature:	> 485 °C			
Self-ignition temperature				
Solid:	n.a.			
Gas:	n.a.			
Decomposition temperature:	n.d.			
Oxidizing properties Not oxidising.				
Vapour pressure:	n.d.			
Density (at 20 °C):	approx. 0,876 g/cm³			
Bulk density:	n.a.			
Water solubility: (at 20 °C)	Miscible			
Partition coefficient n-octanol/water	n.d.			
Viscosity / dynamic: (at 20 °C)	approx. 9 mPa·s			
Viscosity / kinematic:	n.d.			
Flow time:	n.d.			
Relative vapour density:	n.d.			
Evaporation rate:	n.d.			
Solvent separation test:	0 %			
Solvent content:	< 65 %			
9.2. Other information				
No data available				

Revision No: 3,2 - Replaces version: 3,1

according to Regulation (EC) No 1907/2006

Septasol

Revision date: 14.10.2022

Product code: 00320-0160-GHS

Page 6 of 10

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with oxidizing agents.

10.4. Conditions to avoid

Vapour/air mixtures are explosive at intensive warming. Heating can release vapours which can be ignited.

10.5. Incompatible materials

oxidizing agents

10.6. Hazardous decomposition products

No hazardous decomposition products known. Fire may produce: Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No. 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met. No toxicological data available.

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Propan-2-ol)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

11.2. Information on other hazards

Endocrine disrupting properties

No data available

Other information

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

according to Regulation (EC) No 1907/2006

Septasol

Revision date: 14.10.2022

Product code: 00320-0160-GHS

Page 7 of 10

12.2. Persistence and degradability

Propan-2-ol

Readily biodegradable (to OECD criteria).

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Low hazard to waters.

Further information

Do not discharge into surface waters/groundwater.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Where possible recycling is preferred to disposal. Can be incinerated, when in compliance with local regulations.

List of Wastes Code - residues/unused products

070604 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fats, grease, soaps, detergents, disinfectants and cosmetics; other organic solvents, washing liquids and mother liquors; hazardous waste

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land transport (ADR/RID)

<u>14.1. UN number:</u>	UN 1987
14.2. UN proper shipping name:	ALCOHOLS, N.O.S. (Propan-2-ol)
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3
Classification code:	F1
Limited quantity:	5 L / 30 kg
Excepted quantity:	E1
Transport category:	3
Hazard No:	30
Tunnel restriction code:	D/E

according to Regulation (EC) No 1907/2006

Revision date: 14.10.2022	Septasol Product code: 00320-0160-GHS	Page 8 of 1
nland waterways transport (ADN)		
<u>14.1. UN number:</u>	UN 1987	
14.2. UN proper shipping name:	ALCOHOLS, N.O.S. (Propan-2-ol)	
14.3. Transport hazard class(es):	3	
14.4. Packing group:		
Hazard label:	3	
Classification code:	F1	
Limited quantity:	5 L / 30 kg	
Excepted quantity:	E1	
Marine transport (IMDG)		
<u>14.1. UN number:</u>	UN 1987	
14.2. UN proper shipping name:	ALCOHOLS, N.O.S. (propan-2-ol)	
14.3. Transport hazard class(es):	3	
14.4. Packing group:	III	
Hazard label:	3	
Marine pollutant:	No	
Limited quantity:	5 L / 30 kg	
Excepted quantity:	E1	
EmS:	F-E, S-D	
Air transport (ICAO-TI/IATA-DGR)	1014007	
<u>14.1. UN number:</u>		
14.2. UN proper shipping name:	ALCOHOLS, N.O.S. (propan-2-ol)	
14.3. Transport hazard class(es):	3	
14.4. Packing group:	-	
Hazard label:	3	
Limited quantity Passenger:	10 L	
Passenger LQ:	Y344	
Excepted quantity:	E1	
IATA-packing instructions - Passenger: IATA-max. quantity - Passenger:	355 60 L	
IATA-max. quantity - Passenger: IATA-packing instructions - Cargo:	80 L 366	
IATA-max. quantity - Cargo:	220 L	
4.5. Environmental hazards		
ENVIRONMENTALLY HAZARDOUS:	Νο	
4.6. Special precautions for user Take the usual precautions when han	udling with chemicals	
4.7. Maritime transport in bulk according	-	
The transport takes place only in app	roved and appropriate packaging.	
vision No: 3.2 - Replaces version: 3.1	GB - EN	Print date: 17.10.2022

according to Regulation (FC) No 1907/2006

acco	ording to Regulation (EC) No 1907/2006	
	Septasol	
Revision date: 14.10.2022	Product code: 00320-0160-GHS	Page 9 of 10
SECTION 15: Regulatory information		
15.1. Safety, health and environmental regul	ations/legislation specific for the substance or mixture	
EU regulatory information Restrictions on use (REACH, annex XVII): Entry 3, Entry 40, Entry 75		
2004/42/EC (VOC): Information according to 2012/18/EU (SEVESO III):	63 % P5c FLAMMABLE LIQUIDS	
National regulatory information		
Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juven work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.	
Water hazard class (D):	1 - slightly hazardous to water	
15.2. Chemical safety assessment		
For this substance a chemical safety as	ssessment has not been carried out.	
SECTION 16: Other information		
Changes		
RID = Règlement concernant le transpor ADN = Accord européen relatif au transp intérieure IMDG = International Maritime Code for I	Association / International Civil Aviation Organization	
	onstruction and Equipment of Ships Carrying Dangerous Chemicals in B	ulk
GHS = Globally Harmonized System of C REACH = Registration, Evaluation, Author CAS = Chemical Abstract Service EN = European norm ISO = International Organization for Stan DIN = Deutsche Industrie Norm PBT = Persistent Bioaccumulative and T vPvB = Very Persistent and very Bio-acc	orization and Restriction of Chemicals Idardization oxic	
LD = Lethal dose LC = Lethal concentration EC = Effect concentration IC = Median immobilisation concentration		

IC = Median immobilisation concentration or median inhibitory concentration

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product

according to Regulation (EC) No 1907/2006

Septasol			
Revision date: 14.10.2022	Product code: 00320-0160-GHS	Page 10 of 10	
accidents and irregularities. The information describes exclus	n on use and on product), but to liberation of major amounts in cas sively the safety requirements for the product(s) and is based on th		
level of our knowledge. The delivery specifications are c	ontained in the corresponding product sheet.		
This data does not constitute a g warranty regulations.	juarantee for the characteristics of the product(s) as defined by the	e legal	
(n.a. = not applicable; n.d. = not	determined)		

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)