according to Regulation (EC) No 1907/2006

LuxaBond Total Etch (bond A)

Revision date: 15.04.2021 Product code: 2222 Page 1 of 5

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LuxaBond Total Etch (bond A)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Uses advised against

pregnant or breastfeeding people should not work with hazardous substances

1.3. Details of the supplier of the safety data sheet

Company name: DMG Chemisch-Pharmazeutische Fabrik GmbH

Street: Elbgaustraße 248
Place: D-22547 Hamburg

Telephone: +49. (0) 40. 84006-0 Telefax: +49. (0) 40. 84006-222

e-mail: info@dmg-dental.com Internet: www.dmg-dental.com

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Hazard categories:

Serious eye damage/eye irritation: Eye Dam. 1 Respiratory or skin sensitisation: Skin Sens. 1

Hazard Statements:

May cause respiratory irritation.
Causes serious eye damage.
May cause an allergic skin reaction.

2.2. Label elements

Regulation (EC) No 1272/2008

Signal word: Danger

Pictograms:





Hazard statements

H335 May cause respiratory irritation.
 H318 Causes serious eye damage.
 H317 May cause an allergic skin reaction.

Precautionary statements

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P313 Get medical advice/attention.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

chemical characterization (preparation): Acrylate.-resin.

according to Regulation (EC) No 1907/2006

LuxaBond Total Etch (bond A)

Revision date: 15.04.2021 Product code: 2222 Page 2 of 5

Hazardous components

CAS No	Chemical name		Quantity	
	EC No Index No REACH No			
	Classification (Regulation (EC) No 1272/2008)			
1565-94-2	Bis-GMA			15 - 25 %
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, STOT SE 3; H315 H319 H317 H335			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity	
	Specific Conc. L	ific Conc. Limits, M-factors and ATE		
1565-94-2		Bis-GMA	15 - 25 %	
	oral: LD50 = 5000 mg/kg			

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Move victim to fresh air. Put victim at rest and keep warm.

After contact with skin

After contact with skin, wash immediately with: Water and soap.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After ingestion

Call a physician immediately.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water fog. Extinguishing powder. Sand. Foam. Carbon dioxide (CO2).

Unsuitable extinguishing media

High power water jet.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Wear suitable protective clothing. Provide adequate ventilation.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Other information

Take up mechanically.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed. Wear suitable protective clothing and gloves. Avoid contact with eyes.

according to Regulation (EC) No 1907/2006

LuxaBond Total Etch (bond A)

Revision date: 15.04.2021 Product code: 2222 Page 3 of 5

Advice on general occupational hygiene

When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Store only in original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional advice on limit values

To date, no national critical limit values exist.

8.2. Exposure controls



100 °C

Appropriate engineering controls

Ensure adequate ventilation of the storage area.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tightly sealed safety glasses.

Hand protection

Tested protective gloves are to be worn: Suitable material: NBR (Nitrile rubber).

Respiratory protection

The following must be prevented: inhalation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid
Colour: yellow
Odour: like: ester

Changes in the physical state

Boiling point or initial boiling point and

boiling range:
point of decomposition: > 200 °C
Flash point: > 100 °C
pH-Value (at 20 °C): 4.5 - 7

Solubility in other solvents

Solubility ca. 50 %

Vapour pressure: 23 hPa

(at 20 °C)

Density: 1,1 g/cm³
Relative vapour density: > 1

SECTION 10: Stability and reactivity

according to Regulation (EC) No 1907/2006

LuxaBond Total Etch (bond A)

Revision date: 15.04.2021 Product code: 2222 Page 4 of 5

10.4. Conditions to avoid

Light. heat.

10.5. Incompatible materials

Keep away from strong acids, leachates, heavy metal salts and reducing materials.

10.6. Hazardous decomposition products

In case of fire may be liberated: Gas / vapours, irritant. (Acrylate., pungent)

Further information

Substances sensitive to light.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

LD50: Rat 5500mg/kg

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
1565-94-2	Bis-GMA					
		LD50 mg/kg	5000	Rat	literature value	

Irritation and corrosivity

Frequently or prolonged contact with skin may cause dermal irritation.

Irritant effect on the eye: Frequently or prolonged contact with skin may cause dermal irritation.

Sensitising effects

May cause sensitization by skin contact.

Additional information on tests

Contains Methacrylates: May produce an allergic reaction. May cause sensitization by skin contact.

SECTION 12: Ecological information

12.1. Toxicity

Aquatoxicity LC50: > 360 mg / I / 48h

12.2. Persistence and degradability

Product is partially biodegradable. 50%

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Further information

Do not allow to enter into surface water or drains. Leakage into the environment must be prevented.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Can be burnt together with household waste in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.

Carry out a burning of harzardous waste according to official regulations.

according to Regulation (EC) No 1907/2006

LuxaBond Total Etch (bond A)

Product code: 2222 Revision date: 15.04.2021 Page 5 of 5

List of Wastes Code - residues/unused products

WASTES FROM HUMAN OR ANIMAL HEALTH CARE AND/OR RELATED RESEARCH

(EXCEPT KITCHEN AND RESTAURANT WASTES NOT ARISING FROM IMMEDIATE HEALTH

CARE); wastes from natal care, diagnosis, treatment or prevention of disease in humans;

chemicals consisting of or containing hazardous substances; hazardous waste

SECTION 14: Transport information

Other applicable information

No dangerous good in sense of these transport regulations.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3

National regulatory information

Water hazard class (D): - - non-hazardous to water

Causes skin irritation

SECTION 16: Other information

Relevant H and EUH statements (number and full text) U215

11010	Causes skill illitation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.

H335 May cause respiratory irritation.

Further Information

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

Telefax: +49. (0) 40. 84006-222

Safety Data Sheet

according to Regulation (EC) No 1907/2006

LuxaBond Total Etch Bond B

Revision date: 14.04.2016 Product code: 2222 Page 1 of 5

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LuxaBond Total Etch Bond B

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: DMG Chemisch-Pharmazeutische Fabrik GmbH

Street: Elbgaustraße 248
Place: D-22547 Hamburg
Telephone: +49. (0) 40. 84006-0

e-mail: info@dmg-dental.com Internet: www.dmg-dental.com

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Serious eye damage/eye irritation: Eye Dam. 1 Respiratory or skin sensitisation: Skin Sens. 1

Hazard Statements:

May cause respiratory irritation.
Causes serious eye damage.
May cause an allergic skin reaction.

2.2. Label elements

Regulation (EC) No. 1272/2008

Signal word: Danger

Pictograms:





Hazard statements

H335 May cause respiratory irritation.
H318 Causes serious eye damage.
H317 May cause an allergic skin reaction.

Precautionary statements

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P313 Get medical advice/attention.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

chemical characterization (preparation): Acrylate.-resin.

according to Regulation (EC) No 1907/2006

LuxaBond Total Etch Bond B

Revision date: 14.04.2016 Product code: 2222 Page 2 of 5

Hazardous components

CAS No	Chemical name			Quantity	
	EC No	EC No Index No REACH No			
	Classification according to Regulation (EC) No. 1272/2008 [CLP]				
1565-94-2	Bis-GMA			15 - 25 %	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, STOT SE 3; H315 H319 H317 H335				

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Move victim to fresh air. Put victim at rest and keep warm.

After contact with skin

After contact with skin, wash immediately with: Water and soap.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After ingestion

Call a physician immediately.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water fog. Extinguishing powder. Sand. Foam. Carbon dioxide (CO2).

Unsuitable extinguishing media

High power water jet.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear suitable protective clothing. Provide adequate ventilation.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Take up mechanically.

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed. Wear suitable protective clothing and gloves. Avoid contact with eyes.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Store only in original container.

SECTION 8: Exposure controls/personal protection

according to Regulation (EC) No 1907/2006

LuxaBond Total Etch Bond B

Product code: 2222 Revision date: 14.04.2016 Page 3 of 5

8.1. Control parameters

8.2. Exposure controls



Appropriate engineering controls

Ensure adequate ventilation of the storage area.

Protective and hygiene measures

When using do not eat or drink.

Eye/face protection

Tightly sealed safety glasses.

Hand protection

Tested protective gloves are to be worn: Suitable material: NBR (Nitrile rubber).

Respiratory protection

The following must be prevented: inhalation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid Colour: vellow Odour: like: ester

pH-Value (at 20 °C): 4.5 - 7

Changes in the physical state

Initial boiling point and boiling range: 100 °C point of decomposition: > 200 °C > 100 °C Flash point: Vapour pressure: 23 hPa (at 20 °C)

Density: 1,1 g/cm³

Solubility in other solvents

Solubility ca. 50 %

Vapour density: > 1

SECTION 10: Stability and reactivity

10.4. Conditions to avoid

Light. heat.

10.5. Incompatible materials

Keep away from strong acids, leachates, heavy metal salts and reducing materials.

10.6. Hazardous decomposition products

In case of fire may be liberated: Gas / vapours, irritant. (Acrylate., pungent)

Further information

Substances sensitive to light.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

according to Regulation (EC) No 1907/2006

LuxaBond Total Etch Bond B

Revision date: 14.04.2016 Product code: 2222 Page 4 of 5

Acute toxicity

LD50: Rat 5500mg/kg

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
1565-94-2	Bis-GMA					
	oral	LD50 mg/kg	5000	Rat	literature value	

Irritation and corrosivity

Frequently or prolonged contact with skin may cause dermal irritation.

Irritant effect on the eye: Frequently or prolonged contact with skin may cause dermal irritation.

Sensitising effects

May cause sensitization by skin contact.

Additional information on tests

Contains Methacrylates: May produce an allergic reaction. May cause sensitization by skin contact.

SECTION 12: Ecological information

12.1. Toxicity

Aquatoxicity LC50: > 360 mg / I / 48h

12.2. Persistence and degradability

Product is partially biodegradable. 50%

Further information

Do not allow to enter into surface water or drains. Leakage into the environment must be prevented.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Can be burnt together with household waste in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.

Carry out a burning of harzardous waste according to official regulations.

Waste disposal number of waste from residues/unused products

180106 WASTES FROM HUMAN OR ANIMAL HEALTH CARE AND/OR RELATED RESEARCH (EXCEPT

KITCHEN AND RESTAURANT WASTES NOT ARISING FROM IMMEDIATE HEALTH CARE); wastes from natal care, diagnosis, treatment or prevention of disease in humans; chemicals consisting of or containing hazardous substances; hazardous waste

SECTION 14: Transport information

Other applicable information

No dangerous good in sense of these transport regulations.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulatory information

Water contaminating class (D): - - not water contaminating

SECTION 16: Other information

according to Regulation (EC) No 1907/2006

LuxaBond Total Etch Bond B Product code: 2222 Page 5 of 5

Relevant H and EUH statements (number and full text)

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.

Further Information

Revision date: 14.04.2016

-

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)