

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Silagum

Revision date: 17.05.2021

Product code: 5010

Page 1 of 5

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Silagum

1.2. Relevant identified uses of the substance or mixture and uses advised against**Uses advised against**

pregnant or breastfeeding people should not work with hazardous substances

1.3. Details of the supplier of the safety data sheet

Company name:	DMG Chemisch-Pharmazeutische Fabrik GmbH	
Street:	Elbgaustraße 248	
Place:	D-22547 Hamburg	
Telephone:	+49. (0) 40. 84006-0	Telefax: +49. (0) 40. 84006-222
e-mail:	info@dmg-dental.com	
Internet:	www.dmg-dental.com	

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Hazard categories:

Serious eye damage/eye irritation: Eye Irrit. 2

Hazard Statements:

Causes serious eye irritation.

2.2. Label elements**Regulation (EC) No 1272/2008****Signal word:** Warning**Pictograms:****Hazard statements**

H319 Causes serious eye irritation.

Precautionary statements

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

2.3. Other hazards

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Chemical characterization**

Paste

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Silagum

Revision date: 17.05.2021

Product code: 5010

Page 2 of 5

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
68131-39-5	Fatty Alcohol Ethoxylate			< 2.5 %
	Eye Dam. 1, Aquatic Acute 1; H318 H400			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures****After inhalation**

not applicable

After contact with skin

After contact with skin, wash immediately with: Water and soap.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After ingestion

Medical treatment necessary.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**Water fog. Extinguishing powder. Sand. Foam. Carbon dioxide (CO₂).**Unsuitable extinguishing media**

High power water jet.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Wear suitable protective clothing.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up**Other information**

Take up mechanically. Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Keep container tightly closed. Wear suitable protective clothing and gloves. Avoid contact with eyes.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed. Ensure adequate ventilation of the storage area. Store only in original container.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Silagum

Revision date: 17.05.2021

Product code: 5010

Page 3 of 5

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Additional advice on limit values**

To date, no national critical limit values exist.

8.2. Exposure controls**Individual protection measures, such as personal protective equipment****Eye/face protection**

Tightly sealed safety glasses.

Hand protection

Tested protective gloves are to be worn: Suitable material: NBR (Nitrile rubber).

Skin protection

When using do not eat or drink.

Respiratory protection

No risks worthy of mention.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Paste
Colour:	characteristic
Odour:	characteristic
Boiling point or initial boiling point and boiling range:	> 300 °C
Flash point:	> 130 °C
Auto-ignition temperature:	> 400 °C
pH-Value (at 20 °C):	not applicable
Water solubility:	insoluble
Density:	1,2 - 1,7 g/cm ³
Relative vapour density:	> 1

SECTION 10: Stability and reactivity**10.4. Conditions to avoid**

heat.

Decomposition takes place from temperatures above: 100 °C

Decomposition under formation of: Formaldehyde.

10.5. Incompatible materials

After contact with water: Formation of: hydrogen.

10.6. Hazardous decomposition products

hydrogen. Formaldehyde.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Silagum

Revision date: 17.05.2021

Product code: 5010

Page 4 of 5

Acute toxicity

LD50: Rat 5000 mg/kg

Irritation and corrosivity

Irritant effect on the skin: non-irritant.

Irritant effect on the eye: irritant.

SECTION 12: Ecological information**12.1. Toxicity**

Acute fish toxicity LC50: > 200 mg/l/96h

12.2. Persistence and degradability

Preparation not tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Can be burnt together with household waste in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.

List of Wastes Code - residues/unused products

180106 WASTES FROM HUMAN OR ANIMAL HEALTH CARE AND/OR RELATED RESEARCH (EXCEPT KITCHEN AND RESTAURANT WASTES NOT ARISING FROM IMMEDIATE HEALTH CARE); wastes from natal care, diagnosis, treatment or prevention of disease in humans; chemicals consisting of or containing hazardous substances; hazardous waste

SECTION 14: Transport information**Other applicable information**

No dangerous good in sense of these transport regulations.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulatory information**

Water hazard class (D): 1 - slightly hazardous to water

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 2.
re-classification of GHS-CLP labeling (H319)

Relevant H and EUH statements (number and full text)

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Silagum

Revision date: 17.05.2021

Product code: 5010

Page 5 of 5

H400

Very toxic to aquatic life.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

SilagumComfortReliningVarnish

Print date: 07.02.2017

Product code: 5010

Page 1 of 4

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

SilagumComfortReliningVarnish

1.2. Relevant identified uses of the substance or mixture and uses advised against**1.3. Details of the supplier of the safety data sheet**

Company name:	DMG Chemisch-Pharmazeutische Fabrik GmbH	
Street:	Elbgaustraße 248	
Place:	D-22547 Hamburg	
Telephone:	+49. (0) 40. 84006-0	Telefax: +49. (0) 40. 84006-222
e-mail:	info@dmg-dental.com	
Internet:	www.dmg-dental.com	

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Serious eye damage/eye irritation: Eye Irrit. 2

Hazard Statements:

Causes serious eye irritation.

2.2. Label elements**Regulation (EC) No. 1272/2008****Signal word:** Warning**Pictograms:****Hazard statements**

H319 Causes serious eye irritation.

Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Chemical characterization**

Paste

Safety Data Sheet

according to Regulation (EC) No 1907/2006

SilagumComfortReliningVarnish

Print date: 07.02.2017

Product code: 5010

Page 2 of 4

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
68131-39-5	Fatty Alcohol Ethoxylate			< 2.5 %
	Eye Dam. 1, Aquatic Acute 1; H318 H400			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures****After inhalation**

not applicable

After contact with skin

After contact with skin, wash immediately with: Water and soap.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After ingestion

Consult physician.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**Water fog. Extinguishing powder. Sand. Foam. Carbon dioxide (CO₂).**Unsuitable extinguishing media**

High power water jet.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Wear suitable protective clothing.

6.2. Environmental precautions

Do not empty into drains or the aquatic environment.

6.3. Methods and material for containment and cleaning up

Collect mechanically. Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Keep container tightly closed. Wear suitable protective clothing and gloves. Avoid contact with eyes.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed. Ensure adequate ventilation of the storage area. Store only in original container.

SECTION 8: Exposure controls/personal protection

Safety Data Sheet

according to Regulation (EC) No 1907/2006

SilagumComfortReliningVarnish

Print date: 07.02.2017

Product code: 5010

Page 3 of 4

8.1. Control parameters**8.2. Exposure controls****Eye/face protection**

Tightly sealed safety glasses.

Hand protection

Tested protective gloves are to be worn: Suitable material: NBR (Nitrile rubber).

Skin protection

When using do not eat or drink.

Respiratory protection

No risks worthy of mention.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Paste
Colour:	characteristic
Odour:	characteristic

Test method

pH-Value (at 20 °C):	not applicable
----------------------	----------------

Changes in the physical state

Initial boiling point and boiling range:	> 300 °C
Flash point:	> 130 °C
Ignition temperature:	> 400 °C
Density:	1,2 - 1,7 g/cm ³
Water solubility:	insoluble
Vapour density:	> 1

SECTION 10: Stability and reactivity**10.4. Conditions to avoid**

heat.

Decomposition takes place from temperatures above: 100 °C

Decomposition under formation of: Formaldehyde.

10.5. Incompatible materials

On contact with water: Formation of: hydrogen.

10.6. Hazardous decomposition products

hydrogen. Formaldehyde.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity**

LD50: Rat. 5000 mg/kg

Safety Data Sheet

according to Regulation (EC) No 1907/2006

SilagumComfortReliningVarnish

Print date: 07.02.2017

Product code: 5010

Page 4 of 4

Irritation and corrosivity

Irritant effect on the skin: Not an irritant.

Irritant effect on the eye: irritant.

SECTION 12: Ecological information**12.1. Toxicity**

Acute fish toxicity LC50: > 200 mg/l/96h

12.2. Persistence and degradability

Preparation not tested.

Further information

Do not empty into drains or the aquatic environment.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Advice on disposal**

Can be burnt together with household waste in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.

Waste disposal number of waste from residues/unused products

180106 WASTES FROM HUMAN OR ANIMAL HEALTH CARE AND/OR RELATED RESEARCH (except kitchen and restaurant wastes not arising from immediate health care); wastes from natal care, diagnosis, treatment or prevention of disease in humans; chemicals consisting of or containing hazardous substances
Classified as hazardous waste.

SECTION 14: Transport information**Other applicable information**

Not a hazardous material with respect to these transportation regulations.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulatory information**

Water contaminating class (D): 1 - slightly water contaminating

SECTION 16: Other information**Changes**

re-classification of GHS-CLP labeling (H319)

Relevant H and EUH statements (number and full text)

H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H400 Very toxic to aquatic life.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Silagum Comfort Primer

Revision date: 24.01.2020

Product code: 5100

Page 1 of 6

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Silagum Comfort Primer

1.2. Relevant identified uses of the substance or mixture and uses advised against**1.3. Details of the supplier of the safety data sheet**

Company name:	DMG Chemisch-Pharmazeutische Fabrik GmbH		
Street:	Elbgaustraße 248		
Place:	D-22547 Hamburg		
Telephone:	+49. (0) 40. 84006-0	Telefax:	+49. (0) 40. 84006-222
e-mail:	info@dmg-dental.com		
Internet:	www.dmg-dental.com		

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Hazard categories:

Flammable liquid: Flam. Liq. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Highly flammable liquid and vapour.

Causes serious eye irritation.

May cause drowsiness or dizziness.

2.2. Label elements**Regulation (EC) No 1272/2008****Hazard components for labelling**

ethyl acetate

Signal word: Danger**Pictograms:****Hazard statements**

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P240 Ground and bond container and receiving equipment.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Silagum Comfort Primer

Revision date: 24.01.2020

Product code: 5100

Page 2 of 6

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Chemical characterization**

chemical characterization (preparation): Prepolymer(s). ethyl acetate.

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
141-78-6	ethyl acetate			< 97 %
	205-500-4	607-022-00-5		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures****After inhalation**

Move victim to fresh air. Put victim at rest and keep warm.

After contact with skin

After contact with skin, wash immediately with: Water and soap.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After ingestion

Medical treatment necessary.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**Water fog. Extinguishing powder. Sand. Foam. Carbon dioxide (CO₂).**Unsuitable extinguishing media**

High power water jet.

5.2. Special hazards arising from the substance or mixture

Formation of explosive mixtures with: Air.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove all sources of ignition. Provide adequate ventilation.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up**Other information**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

SECTION 7: Handling and storage

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Silagum Comfort Primer

Revision date: 24.01.2020

Product code: 5100

Page 3 of 6

7.1. Precautions for safe handling**Advice on safe handling**

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.
Use explosion-proof machinery, apparatus, ventilation facilities, tools etc.

Further information on handling

Wear suitable gloves. Avoid contact with eyes.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep only in the original container in a cool, well-ventilated place.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
141-78-6	Ethyl acetate	200	734		TWA (8 h)	
		400	1468		STEL (15 min)	

Additional advice on limit values

MAK 400 ppm (ethyl acetate.)

8.2. Exposure controls**Appropriate engineering controls**

Provide adequate ventilation.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Tightly sealed safety glasses.

Hand protection

Tested protective gloves are to be worn: Suitable material: NBR (Nitrile rubber).

Skin protection

When using do not eat or drink.

Respiratory protection

Do not breathe gas/vapour. Filtering device (full mask or mouthpiece) with filter: A

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	liquid
Colour:	yellow
Odour:	characteristic
Boiling point or initial boiling point and boiling range:	> 80 °C
Lower explosion limits:	2,0 vol. %
Upper explosion limits:	11,5 vol. %
Flash point:	Mixture not tested.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Silagum Comfort Primer

Revision date: 24.01.2020

Product code: 5100

Page 4 of 6

Auto-ignition temperature:	> 460 °C
pH-Value (at 20 °C):	7
Water solubility:	80 g/L
Vapour pressure:	100 hPa
Density:	0,9 g/cm ³
Relative vapour density:	> 1

SECTION 10: Stability and reactivity**10.4. Conditions to avoid**

heat.

Decomposition takes place from temperatures above: 80°C (boiling temperature / boiling range)

10.5. Incompatible materials

Oxidizing agents. peroxides. acid.

10.6. Hazardous decomposition products

In case of fire may be liberated: Gas / vapours, irritant. (pungent)

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

LD50: Rat 5000 mg/kg

Irritation and corrosivity

Irritant effect on the skin: prolonged action.

Irritant effect on the eye: irritant.

SECTION 12: Ecological information**12.1. Toxicity**

Acute fish toxicity LC50: > 333 mg/l/48h (ethyl acetate.)

12.2. Persistence and degradability

Product is biodegradable. (ethyl acetate.)

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Can be burnt together with household waste in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.

List of Wastes Code - residues/unused products

180106 WASTES FROM HUMAN OR ANIMAL HEALTH CARE AND/OR RELATED RESEARCH (EXCEPT KITCHEN AND RESTAURANT WASTES NOT ARISING FROM IMMEDIATE HEALTH CARE); wastes from natal care, diagnosis, treatment or prevention of disease in humans; chemicals consisting of or containing hazardous substances; hazardous waste

SECTION 14: Transport information**Land transport (ADR/RID)**

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Silagum Comfort Primer

Revision date: 24.01.2020

Product code: 5100

Page 5 of 6

14.1. UN number or ID number: UN 1173
14.2. UN proper shipping name: ETHYL ACETATE
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Classification code: F1
 Limited quantity: 1 L
 Transport category: 2
 Hazard No: 33
 Tunnel restriction code: D/E

Other applicable information (land transport)

E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1173
14.2. UN proper shipping name: ETHYL ACETATE
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Special Provisions: -
 Limited quantity: 1 L
 EmS: F-E, S-D

Other applicable information (marine transport)

E2

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1173
14.2. UN proper shipping name: ETHYL ACETATE
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Limited quantity Passenger: 1 L
 IATA-packing instructions - Passenger: 353
 IATA-max. quantity - Passenger: 5 L
 IATA-packing instructions - Cargo: 364
 IATA-max. quantity - Cargo: 60 L

Other applicable information (air transport)

E2

: Y341

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

SECTION 15: Regulatory information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Silagum Comfort Primer

Revision date: 24.01.2020

Product code: 5100

Page 6 of 6

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 8.

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)